according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page1/11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name: Kölner Classic Zaponlack

**UFI:** GYJD-33HM-800E-3P6M

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint

### 1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier: KVP Kölner Vergolderprodukte GmbH · Schwabach GERMANY Telephone: +49 (0) 35 1 - 86 26 89 50 · Telefax: +49 (0) 35 1 - 86 26 34 91

Wepsite: http://kolner-vergolderprodukte.de/
E-Mail : info@kolner-vergolderprodukte.de

### 1.4. Emergency telephone number:

+49 (0) 35 1 - 86 26 89 50 (only during offices hours)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page2/11

#### 2.2. Label elements

·Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

·Hazard pictograms





· Signal word Warning

### · Hazard-determining components of labelling:

n-Butylacetat

Xylol

2,6-Dimethyl-heptan-4-one

· Hazard statements

H226 Flammable liquid and vapour. H315 Causes skin irritation. Causes

H319 serious eye irritation

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

*P*210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

P261 sources. No smoking.

P280 Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Additional information:

EUH208 Contains Methyl methacrylate, n-butyl methacrylate, dodecane-1-thiol. May produce an allergic reaction

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable..

### SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 3/11

· Dangerous components		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butylacetate  Trianskip Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene  ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 108-83-8 EINECS: 203-620-1 Reg.nr.: 01-2119474441-41	2,6-dimethylheptan-4-one	2,5-<10%
CAS: 763-69-9 EINECS: 212-112-9 Reg.nr.: 01-2119463267-34	Ethyl 3-ethoxypropionate  Flam. Liq. 3, H226, EUH066	2,5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzenel  Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2,5%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	Methyl-methacrylat  Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≥</i> 0,1-<1%
CAS: 97-88-1 EINECS: 202-615-1 Reg.nr.: 01-2119486394-28	n-Butyl-methacrylat  Trit. 2, H315; Eye Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335	<i>≥</i> 0,1-<1%
CAS: 112-55-0 EINECS: 203-984-1	dodecane-1-thioll  Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,	≥0,025-<0,1%

H410 (M=1); Skin Sens. 1A, H317

### Additional information:

For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- •4.1 Description of first aid measures
- •General information: Immediately remove any clothing soiled by the product.
- •After inhalation: Supply fresh air; consult doctor in case of complaints.
- •After skin contact: Immediately rinse with water.
- •After eye contact: Rinse opened eye for several minutes under running water.
- ·After swallowing: If symptoms persist consult doctor.
- •4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- ·4.3 Indication of any immediate medical attention and special treatment needed
- ·No further relevant information available.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page4/11

# **SECTION 5: Firefighting measures**

- ·5.1 Extinguishing media
- ·Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- ·For safety reasons unsuitable extinguishing agents: Water with full jet
- ·5.2 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- ·5.3 Advice for firefighters
- •Protective equipment: No special measures required.

·SECTION 6: Accidental release measures

·6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

·6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

·6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

### -6.4 Reference to other sections

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- · See Section 13 for disposal information.

### SECTION 7: Handling and storage

### •7.1 Precautions for safe handling

Use only in well ventilated areas.

·Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols

·Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- ·7.2 Conditions for safe storage, including any incompatibilities
- ·Storage:
- •Requirements to be met by storerooms and receptacles No special requirements.
- •Information about storage in one common storage facility: Store away from foodstuffs.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 5/11

### ·Further information about storage conditions:

·Keep container tightly sealed.

·Storage class: 3

·7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

	dients with limit values that require monitoring at the workplace:
123-8	6-4 n-Butylacetat
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
1330	20-7 Xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
108-8	3-8 2,6-Dimethyl-heptan-4-one
WEL	Long-term value: 148 mg/m³, 25 ppm
100-4	1-4 Ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
80-62	-6 Methyl-methacrylate
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm
	·

### · Ingredients with biological limit values:

1330-20-7 Xylene

BMGW 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 6/11

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls Appropriate engineering controls
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

- · Immediately remove all soiled and contaminated clothing
- · Wash hands before breaks and at the end of work.
- · Avoid contact with the eyes.
- · Avoid contact with the eyes and skin.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

- · Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level ≤ 2

· Eye/face protection



Tightly sealed goggles



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 7/11

## SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties General Information

· Physical state Fluid

Colour: According to product specification
Odour: Characteristic

Odour:
Characteristic
Not determined.
Melting point/freezing point:
Undetermined.

Boiling point or initial boiling point and boiling range 124-128 °C (123-86-4 n-Butyl acetate)

Flammability Flammable.

Lower and upper explosion limit

Lower: 1.2 Vol % (123-86-4 n-Butyl acetate)

 • Upper:
 7.5 Vol % (123-86-4 n-Butyl acetate)

 • Flash point:
 24 °C (DIN 53213)

· Auto-ignition temperature: 345 °C (DIN 51794, 108-83-8 2,6-dimethylheptan-

Decomposition temperature: 4-one)
Not determined.

PH Not determined.

· Viscosity: · Kinematic viscosity at 20 °C 110 s

Kinematic viscosity at 20 °C
 Dynamic:
 Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value)
Not determined.

Vapour pressure at 20 °C:
10.7 hPa (123-86-4 n-Butyl acetate)

Vapour pressure at 50 °C: 55 hPa

Density and/or relative density

Density at 20 °C:
Relative density
Vapour density

0.97 g/cm³ (DIN 53217)
Not determined.
Not determined.

9.2 Other information

Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 51.47 % · Solids content (weight-%): 48.5 %

Observative and title a

· Change in condition

· Evaporation rate Not determined.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 8/11

Information with regard to physical hazard classes

· Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void

Flammable liquids Flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which emit
flammable gases in contact with water
Void

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Oesensitised explosives
Void
Void
Void
Void
Void
Void

### **SECTION 10: Stability and reactivity**

- · 10.1 **Reactivity** No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 9/11

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

### **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shippong name ADR IMDG, IATA

**UN1263 PAINT PAINT** 

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

Label

· IMDG, IATA



· Class 3 Flammable liquids. · Label



3

according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 10/11

14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	13.
ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks:	5L 3 D/E ≤ 450 l: 2.2.3.1.5 ADR
IMDG Limited quantities (LQ) Remarks:	<i>5L</i> ≤ 450 l: 2.3.2.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT. 3. III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Regulated explosives precursors
- · None of the ingredients is listed.
- · Regulated poisons
- · None of the ingredients is listed.
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %	
NK	50-100	

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to UK REACH · Revision: 20.07.2025 · Print: 20.07.2025 Version number 23 (replaces version 22) · Page 11/11

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

### \* Data compared to the previous version altered.

