

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 1/12

Kölner Classic Zaponlack GL Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation:

Kölner Classic Zaponlack GL Spray

UFI:

8Y60-50PJ-R00R-EM6J

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Clear coating material, Varnish.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KVP Kölner Vergolderprodukte GmbH

Rennmühle 3

91126 Schwabach

GERMANY

Telephone: +49 351 86268950

Telefax: +49 351 86263491

E-mail: info@kolner-vergolderprodukte.de

Website: http://kolner-vergolderprodukte.de

E-mail (competent person): info@kolner-vergolderprodukte.de

1.4 Emergency phone number

24h: +49 551 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation
aerosol dispensers and lighters (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	Test data
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	Calculation
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	Calculation
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	Calculation
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure. (auditory organs)	Calculation
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	Calculation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 2/12

Köln Classic Zaponlack GL Spray

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS08
Health hazard



GHS07
Exclamation mark

Signal word: Danger

Listing of ingredients:

xylene; ethylbenzene; acetone; hydrocarbons, C9, aromatics

Hazard statements for physical hazards	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
Hazard statements for health hazards	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure. (auditory organs)
Hazard statements for environmental hazards	
H412	Harmful to aquatic life with long lasting effects.
Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	
P102	Keep out of reach of children.
Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
Precautionary statements Response	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
Precautionary statements Storage	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Precautionary statements Disposal	
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3 Other hazards

No data available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 3/12

Kölner Classic Zaponlack GL Spray

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Ingredients:

Product identifiers	Substance name Classification according to Regulation (EC) No. 1272/2008 [CLP]	Content
CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	25 - 50 weight-%
CAS No.: 74-98-6 EC No.: 200-827-9 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger Acute Toxicity Estimate ATE (inhalation, gases) > 20 mg/L	10 - 25 weight-%
CAS No.: 1330-20-7 EC No.: 215-535-7 REACH No.: 01-2119486136-34	xylene Acute Tox. 4 (H312, H332), Asp. Tox. 1 (H304), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315) Danger Acute Toxicity Estimate ATE (dermal) 1,100 mg/kg ATE (inhalation, vapour) 11 mg/L ATE (inhalation, dust/mist) 1.5 mg/L	10 - < 15 weight-%
CAS No.: 128601-23-0 EC No.: 918-668-5 REACH No.: 01-2119455851-35	hydrocarbons, C9, aromatics Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336) Danger	5 - < 10 weight-%
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	isobutane Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger	2.5 - < 10 weight-%
CAS No.: 106-97-8 EC No.: 203-448-7 REACH No.: 01-2119474691-32	butane Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger	2.5 - < 10 weight-%
CAS No.: 100-41-4 EC No.: 202-849-4 REACH No.: 01-2119489370-35	ethylbenzene Acute Tox. 4 (H332), Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT RE 2 (H373) Danger Acute Toxicity Estimate ATE (inhalation, vapour) 11 mg/L ATE (inhalation, dust/mist) 1.5 mg/L	2.5 - < 10 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing immediately. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. Get medical advice/attention if you feel unwell.

In case of skin contact:

Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 4/12

Kölner Classic Zaponlack GL Spray

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Following ingestion:

Rinse mouth. Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. May cause respiratory irritation. Causes serious eye irritation. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, extinguishing powder, carbon dioxide (CO₂).

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Heating causes rise in pressure with risk of bursting. Vapours can form explosive mixtures with air.

Hazardous combustion products:

In case of fire may be liberated: carbon oxides (CO_x); gases/vapours, toxic.

5.3 Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Heating causes rise in pressure with risk of bursting. Move undamaged containers from immediate hazard area if it can be done safely. Beware of reignition. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Personal precautions:

Eliminate all ignition sources if safe to do so. Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour/aerosol. Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection. See section 8.

6.1.2 For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For containment:

Wipe with absorbent material (e.g. cloth, fleece). In case and large quantities: Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up:

Water with tenside additive, White spirit

6.4 Reference to other sections

Safe handling: see section 7.

Personal protection equipment: see section 8.

Disposal: see section 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 5/12

Köln Classic Zaponlack GL Spray

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Advices on safe handling:

Provide adequate ventilation as well as local exhaust at critical locations. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not breathe gas/vapour/aerosol. Avoid contact with eyes and skin. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge.

Environmental precautions:

Discharge into the environment must be avoided.

Advices on general occupational hygiene

When using do not eat, drink or smoke. Take off contaminated clothing and wash it before reuse. Avoid contact with eyes and skin. Wash hands and face before breaks and after work and take a shower if necessary.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight.

Requirements for storage rooms and vessels:

Floors should be impervious, resistant to liquids and easy to clean. Keep/Store only in original container.

Hints on storage assembly:

Keep away from combustible material. Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

Recommendation:

Clear coating material, Varnish.

SECTION 8: Exposure controls / Personal protection

8.1 Control Parameters

8.1.1 Occupational exposure limit values

Limit value type (country)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³)
IOELV (EU)	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
IOELV (EU)	ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	① 100 ppm (442 mg/m ³) ② 200 ppm (884 mg/m ³) ⑤ (may be absorbed through the skin)

8.1.2 Biological limit values

No data available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 6/12

Kölner Classic Zaponlack GL Spray

8.1.3 DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1,210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	200 mg/m ³	① DNEL consumer ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	2,420 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	186 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg	① DNEL consumer ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg	① DNEL consumer ② Long-term - oral, systemic effects

Substance name	PNEC value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	10.6 mg/L	① PNEC aquatic, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1.06 mg/L	① PNEC aquatic, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	100 mg/L	① PNEC sewage treatment plant
acetone CAS No.: 67-64-1 EC No.: 200-662-2	30.4 mg/kg	① PNEC sediment, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	3.04 mg/kg	① PNEC sediment, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	21 mg/L	① PNEC aquatic, intermittent release
acetone CAS No.: 67-64-1 EC No.: 200-662-2	33.3 mg/kg	① PNEC soil, freshwater

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. Technical ventilation of workplace / Provide adequate ventilation as well as local exhaustion at critical locations.

8.2.2 Personal protection equipment



Eye/face protection:

Eye glasses with side protection (EN 166).

Skin protection:

Wear suitable gloves (EN ISO 374).

Suitable material: IIR (Butyl rubber)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 7/12

Köln Classic Zaponlack GL Spray

Material thickness: $\geq 0,7$ mm

Breakthrough time: 480 min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Respiratory protection:

Usually no personal respiratory protection necessary. Provide adequate ventilation. If workplace limits are exceeded, a respiratory protection approved for this particular job must be worn. Suitable respiratory protection apparatus: Combination filtering device (EN 14387), Filter type A-P2.

Other protection measures:

Wear anti-static footwear and clothing

8.2.3 Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: liquid

Form: Aerosol (liquid)

Colour: transparent

Odour: like Acetone, Hydrocarbons

Flammability: Yes

Safety relevant basic data

Parameter	Value	at	① Method ② Remark
pH	<i>Not applicable.</i>		
Melting point	<i>No data available.</i>		
Freezing point	<i>Not applicable.</i>		
Initial boiling point and boiling range	-44.5 °C		
Flash point	<i>Not applicable.</i>		
Evaporation rate	<i>No data available.</i>		
Auto-ignition temperature	365 °C		
Upper/lower Flammability or explosive limits	1.1 - 13 Vol-%		
Vapour pressure	83 hPa	20 °C	② Propane
Vapour density	<i>Not applicable.</i>		
Density	0.749 g/mL	20 °C	
Bulk density	<i>Not applicable.</i>		
Water solubility	Immiscible	20 °C	
Dynamic viscosity	<i>Not applicable.</i>		
Kinematic viscosity	<i>Not applicable.</i>		

9.2 Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions. Possibility of hazardous reactions/Exothermic reaction with: Oxidising agent, aldehydes, Alkali (Iye), Acids.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 8/12

Kölner Classic Zaponlack GL Spray

10.4 Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Heating causes rise in pressure with risk of bursting.

10.5 Incompatible materials

Highly oxidising substances

10.6 Hazardous decomposition products

No known hazardous decomposition products. In case of fire may be liberated: carbon oxides (COx); gases/vapours, toxic.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

acetone	CAS No.: 67-64-1	EC No.: 200-662-2
LC₅₀ Acute inhalation toxicity (vapour): 76 mg/L 4 h (Rat)		
propane	CAS No.: 74-98-6	EC No.: 200-827-9
LC₅₀ Acute inhalation toxicity (gas): >20 mg/L 4 h (Rat)		

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

Assessment/classification:

No data available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 9/12

Kölner Classic Zaponlack GL Spray

12.2 Persistence and degradability

Biodegradation:

Readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Product/Packaging disposal

Waste codes/waste designations according to EWC

Waste code product

08 01 11 *	Waste paint and varnish containing organic solvents or other dangerous substances
16 05 04 *	Gases in pressure containers (including halons) containing hazardous substances

*: Evidence for disposal must be provided.

Waste code packaging

15 01 04	metallic packaging
----------	--------------------

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Completely emptied packages can be recycled.

Other disposal recommendations:

The allocation of waste code numbers / waste names must be carried out in accordance with the European Waste Catalogue (EWC). Do not allow to enter into surface water or drains. Collect in closed and suitable containers for disposal. Waste for disposal is to be classified and labelled.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI-/IATA-DGR)
14.1 UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2 UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1
14.4 Packing group			
		-	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 10/12

Kölner Classic Zaponlack GL Spray

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI-/IATA-DGR)
14.5 Environmental hazards			
No	No	No	No
14.6 Special precautions for user			
No data available.	No data available.	No data available.	No data available.

14.7 Maritime transport in bulk according to IMO instruments

not relevant

Additional information:

ADR/RID/ADN: Classification code: 5F

Transport as "Limited Quantity" according to chapter 3.4 ADR/RID.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU legislation

Authorisations:

Contains no substances listed in REACH Annex XIV.

Restrictions on use:

Use restriction according to REACH annex XVII, no.: 3

Other regulations (EU):

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

The product does not contain substances of very high concern (SVHC) $\geq 0,1$ %.

VOC content (EU, CH): 88,74 %

15.1.2 National regulations

No data available.

15.2 Chemical Safety Assessment

No data available.

SECTION 16: Other information

16.1 Indication of changes

No data available.

16.2 Abbreviations and acronyms

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC₅₀ = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IC₅₀ = Inhibition concentration, 50%

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 11/12

Kölner Classic Zaponlack GL Spray

IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
LC₅₀ = Lethal concentration, 50%
LD₅₀ = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Content
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Content
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value - time-weighted average
TLV®STEL = Threshold limit value - short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Key literature references and sources for data

European Chemicals Agency (ECHA): <https://www.echa.europa.eu>
ECHA, C&L Inventory: <https://echa.europa.eu/information-on-chemicals/cl-inventory-database>
ECHA, Registered substances: <https://echa.europa.eu/information-on-chemicals/registered-substances>
GESTIS, Information system on hazardous substances: <https://www.gestis.dguv.de/search>
GESTIS, International Limit Values: <https://limitvalue.ifa.dguv.de>
Hörath Gefährliche Stoffe und Gemische, 8. Auflage, Dr. Angela Schulz
Safety data sheets of the manufacturers

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No. 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation
aerosol dispensers and lighters (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	Test data
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	Calculation
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	Calculation
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	Calculation
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure. (auditory organs)	Calculation
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	Calculation

16.5 List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Jul 2026

Print date: 2 Jul 2026

Version: 1.0



Page 12/12

Köln Classic Zaponlack GL Spray

Hazard statements	
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

No data available.

16.7 Additional information

The information in this safety data sheet has been established to our best knowledge and was up-to-date at time of revision. The information is intended to give you advice about the safe handling of the product for storage, processing, transport and disposal. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.